

DAFTAR PUSTAKA

- [1] S. Grainger and J. Blunt, *Engineering Coatings*. Elsevier, 1998.
- [2] F. D. Munthe, “Pengukuran Ketebalan serta Posisi Cacat pada Sampel Carbon Steel dan Stainless Steel dengan Metode Ultrasonic Testing,” *Physics Student Journal*, vol. 2, no. 1, pp. 502–510, Jan. 2015, [Online]. Available: <http://physics.studentjournal.ub.ac.id/index.php/psj/article/view/218/127>
- [3] X. Hu and W. Yang, “Planar capacitive sensors – designs and applications,” *Sensor Review*, vol. 30, no. 1, pp. 24–39, Jan. 2010, doi: 10.1108/02602281011010772.
- [4] A. Yuditama, “Pembuatan Sistem Sensor Kapasitif Untuk Optimasi Lapisan Ketebalan Coating.” Nov. 21, 2022. Accessed: Jan. 01, 2023. [Online]. Available: <https://eprints.untirta.ac.id/id/eprint/17438>
- [5] T. Chen and N. Bowler, “Design of interdigital spiral and concentric capacitive sensors for materials evaluation,” *AIP Conference Proceedings*, Jan. 2013, doi: 10.1063/1.4789232.
- [6] D. Kristianto and W. H. A. Putera, “Studi Penentuan Panjang dan Kedalaman Retak Sambungan Las pada Konstruksi Kapal Menggunakan Pengujian Ultrasonik dengan Variasi Frekuensi dan Ukuran Kristal dan Variasi Kondisi Permukaan Coating dan Uncoating,” DOAJ (DOAJ: Directory of Open Access Journals), Mar. 2013, [Online]. Available: <https://doaj.org/article/576dcf82a0ed4ea1825b84a7181f204e>
- [7] A. Bernieri, L. Ferrigno, M. Laracca, A. Rasile, and M. Ricci, “Ultrasonic NDT on aluminum bars: An experimental performance comparison of excitation and processing techniques,” *Measurement*, vol. 128, pp. 393–402, Nov. 2018, doi: 10.1016/j.measurement.2017.10.040.
- [8] S. Jokosisworo and H. Yudo, “Proses Pengujian Tidak Merusak,” vol. 4, no. 1, pp. 26–30, Mar. 2012, doi: 10.14710/kpl.v4i1.2657.
- [9] M. Jamil et al., “Internal Cracks and Non-Metallic Inclusions as Root Causes of Casting Failure in Sugar Mill Roller Shafts,” *Materials*, vol. 12, no. 15, p. 2474, Aug. 2019, doi: 10.3390/ma12152474.
- [10] Hijazi, A., *Ultrasonic Testing*, Applied Welding Engineering, vol. 293–304. 2012.
- [11] B. Arsada, “Aplikasi Sensor Ultrasonik Untuk Deteksi Posisi Jarak Pada Ruang Menggunakan Arduino Uno,” Deleted Journal, vol. 6, no. 2, Jun. 2017, [Online]. Available: <https://jurnal.unesa.ac.id/index.php/16/article/view/19511>

- [12] I. Lestari, M. Wahyu, R. M. Asmoro, "Measurement of Paint Thickness Using Ultrasonic Sensor," *Journal of Physics: Conference Series*, vol. 1371, no. 1, pp. 1–6, 2019.
- [13] Sari, DassyAnaLaila, "Pengukuran Ketebalan Plat Single Dan Multilayer Menggunakan Ultrasonik Dengan Metode Time Of Flight Diffraction (Tofd) Dan Pulse Echo Berbasis Labview." Feb. 09, 2017. Accessed: Jun. 01, 2023. [Online]. Available: <http://repository.ub.ac.id/id/eprint/155182>
- [14] P. Ripka, J. Blažek, M. Mirzaei, P. Lipovský, M. Šmelko, and K. Draganová, "Inductive Position and Speed Sensors," *Sensors*, vol. 20, no. 1, p. 65, Dec. 2019, doi: 10.3390/s20010065.
- [15] M. R. Gaitonde & R. M. Patrikar, "Inductive sensor for non-destructive measurement of thickness of thin conductive films," *Sensors and Actuators A: Physical*, vol. 123–124, pp. 71–77, 2005.
- [16] R. Setiawan, M. Rivai, and S. Suwito, "Implementasi Analog Front End Pada Sensor Kapasitif Untuk Pengaturan Kelembaban Menggunakan Mikrokontroller STM32," *Jurnal Teknik/Jurnal Teknik ITS*, vol. 5, no. 2, Feb. 2017, doi: 10.12962/j23373539.v5i2.16416.
- [17] E. Terzic, J. Terzic, R. Nagarajah, and M. Alamgir, A Neural Network Approach to Fluid Quantity Measurement in Dynamic Environments. 2012. doi: 10.1007/978-1-4471-4060-3.
- [18] S. Mujib, "Perancangan Sensor Kelembaban Beras Berbasis Kapasitor," Feb. 2013, [Online]. Available: <http://digilib.its.ac.id/public/ITS-paper-26117-1108100065-Paper.pdf>
- [19] L. K. Baxter, *Capacitive Sensors: Design and Applications*. 1996. [Online]. Available: <https://ci.nii.ac.jp/ncid/BA67560151>
- [20] R. Zeng, S. Zhang, H. Chen, and J. Hu, "A capacitive sensor for thickness measurement of thin film coatings," *Journal of Physics: Conference Series*, vol. 1397, no. 6, p. 062062, 2019.
- [21] W. Yao, L. Guo, X. Zhang, and S. Zhang, "A high-precision capacitive sensor for measuring the thickness of coating," *Measurement*, vol. 146, pp. 317–324, 2019.
- [22] Parental, E. T. et al., "Key Concepts," *Key Concepts*, pp. 1–41, 2008.
- [23] Bakhsí, U. A. & Bakhsí, A. O, *Electromagnetic Field Theory*. India: Technical Publications Pune, 2008.

- [24] Maulandari, E. Z., Analisis Hasil Pengukuran Impedansi Listrik Dengan Menggunakan Metode Injeksi Arus Tipe Floating Dan Howland. Malang: Skripsi UB, 2018.
- [25] K. Patel, P. S. Negi, and P. C. Kothari, “Complex S-parameter measurement and its uncertainty evaluation on a vector network analyzer,” *Measurement*, vol. 42, no. 1, pp. 145–149, Jan. 2009, doi: 10.1016/j.measurement.2008.04.010.
- [26] COMSOL Multiphysics, Comsol Multiphysics Reference Manual, Version 5.5. Manual, 2014. [Online]. Available: https://doc.comsol.com/5.5/doc/com.comsol.help.comsol/COMSOL_ReferenceManual.pdf
- [27] COMSOL Multiphysics, “AC / DC Module,” in User ’ s Guide’, © 1998–2019, 2019, p. 300. [Online]. Available: <https://doc.comsol.com/5.4/doc/com.comsol.help.acdc/ACDCModuleUsersGuide.pdf>
- [28] “An Introduction to the Theory of Electrostatics,” Feb. 14, 2019. <https://www.comsol.com/multiphysics/electrostatics-theory> (accessed Jun. 01, 2023).
- [29] T. Su et al., “Wideband optical vector network analyzer based on polarization modulation,” *Optics Communications*, vol. 437, pp. 67–70, Apr. 2019, doi: 10.1016/j.optcom.2018.12.046.
- [30] A. D. Setyowati, D. Darmawan, and A. Suhendi, “Penentuan Parameter Sensor Pelat Sebidang Secara Eksperimental Untuk Mengukur Kapasitansi Bahan Kayu Dan Logam,” eProceedings of Engineering, vol. 6, no. 2, Aug. 2019, [Online]. Available:<https://libraryeproceeding.telkomuniversity.ac.id/index.php/engineering/article/view/9693>
- [31] M. A. Mansor, M. Takeuchi, M. Nakajima, Y. Hasegawa, and M. R. Ahmad, “Electrical Impedance Spectroscopy for Detection of Cells in Suspensions Using Microfluidic Device with Integrated Microneedles,” *Applied Sciences*, vol. 7, no. 2, p. 170, Feb. 2017, doi: 10.3390/app7020170.
- [32] D. Kumar, A. Banerjee, S. Patil, and A. K. Shukla, “A 1 V supercapacitor device with nanostructured graphene oxide/polyaniline composite materials,” *Bulletin of Materials Science/Bulletin of Materials Science*, vol. 38, no. 6, pp. 1507–1517, Oct. 2015, doi: 10.1007/s12034-015-0966-0.
- [33] Y. Sun, Y. Wang, Z. Wang, C. Li, X. Meng, and Y. Qi, “The Influence of Mechanical Properties of Dielectric Material and Structure of Electrodes on Capacitive Sensor Properties,” Aug. 2018, doi: 10.1109/icept.2018.8480422.

- [34] Y. Zhang, L. Wang, dan Y. Wang, “The Effect of Dielectric Thickness on the Capacitance of a Planar Capacitor,” IEEE Transactions on Dielectrics and Electrical Insulation, 2004.
- [35] E. Simbolon, “Eksperimen Metode Ultrasonik Untuk Mengukur Ketebalan Setiap Lapisan Tanah Yang Berbentuk Granular,” eProceedings of Engineering, vol. 8, no. 5, Sep. 2021, [Online]. Available: <https://openlibrarypublications.telkomuniversity.ac.id/index.php/engineering/article/view/16013>