

## DAFTAR PUSTAKA

- [1] E. S. Wagola, “Manfaat Pemakaian Glass Fiber Reinforced Polimer (GFRP) pada Komponen Struktur Saluran Pracetak U-Ditch,” Feb. 14, 2022. doi: 10.31219/osf.io/zdukv.
- [2] Lilin Hermawati, Sunu Arsy Pratomo, and Sugeng Hariyadi, “Penambahan Berat Sic Pada Komposit Matrik Aluminium Dalam Sifat Fisis Dan Mekanis Diperkuat Tib Sebagai Penghalus Butir,” *J. Penelit. Rumpun Ilmu Tek.*, vol. 2, no. 2, pp. 200–211, Jun. 2023, doi: 10.55606/juprit.v2i2.1968.
- [3] K. R. Ahmad, S. B. Jamaluddin, L. B. Hussain, and Z. A. Ahmad, “The Influence of Alumina Particle Size on Sintered Density and Hardness of Discontinuous Reinforced Aluminum Metal Matrix Composite,” *J. Teknol.*, Feb. 2012, doi: 10.11113/jt.v42.732.
- [4] N. H. Husain, A. H. Ahmad, and M. M. Rashidi, “An overview of thixoforming process,” *IOP Conf. Ser. Mater. Sci. Eng.*, vol. 257, p. 012053, Oct. 2017, doi: 10.1088/1757-899X/257/1/012053.
- [5] N. Nayiroh, “Teknologi Material Komposit”.
- [6] S. A. Rahmawaty, “Analisa Kekuatan Tarik dan Tekuk pada Komposit Fiberglass-Polyester Berpenguat Serat Gelas dengan Variasi Fraksi Volume Serat,” *JTM-ITI J. Tek. Mesin ITI*, vol. 5, no. 3, p. 146, Dec. 2021, doi: 10.31543/jtm.v5i3.685.
- [7] R. F. Gibson, *Principles of Composite Material Mechanics*, 0 ed. CRC Press, 2007. doi: 10.1201/9781420014242.
- [8] M. E. Rahmasita, Moh. Farid, and H. Ardhyanta, “Analisa Morfologi Serat Tandan Kosong Kelapa Sawit Sebagai Bahan Penguat Komposit Absorpsi Suara,” *J. Tek. ITS*, vol. 6, no. 2, pp. A787–A792, Oct. 2017, doi: 10.12962/j23373539.v6i2.24332.
- [9] A. Mortensen and J. Llorca, “Metal Matrix Composites,” *Annu. Rev. Mater. Res.*, vol. 40, no. 1, pp. 243–270, Jun. 2010, doi: 10.1146/annurev-matsci-070909-104511.

- [10] I. W. Donald and P. W. McMillan, "Ceramic-matrix composites," *J. Mater. Sci.*, vol. 11, no. 5, pp. 949–972, May 1976, doi: 10.1007/BF00542312.
- [11] R.-M. Wang, S.-R. Zheng, and Y.-P. Zheng, *Polymer matrix composites and technology*. Woodhead Publishing Limited, 2011. doi: 10.1533/9780857092229.
- [12] P. Garg, A. Jamwal, D. Kumar, K. K. Sadasivuni, C. M. Hussain, and P. Gupta, "Advance research progresses in aluminium matrix composites: manufacturing & applications," *J. Mater. Res. Technol.*, vol. 8, no. 5, pp. 4924–4939, Sep. 2019, doi: 10.1016/j.jmrt.2019.06.028.
- [13] K. Z. Hidayat, U. Budiarto, and K. Kiryanto, "Analisis Variasi Sudut Kampuh Single V-Butt Joint Las Mig pada Alumunium 6061 terhadap Kekuatan Tarik dan Kekerasan," *J. Tek. Perkapalan*, vol. 9, no. 1, Art. no. 1, Oct. 2020.
- [14] T. V. Christy, N. Murugan, and S. Kumar, "A Comparative Study on the Microstructures and Mechanical Properties of Al 6061 Alloy and the MMC Al 6061/TiB<sub>2</sub>/12<sub>p</sub>," *J. Miner. Mater. Charact. Eng.*, vol. 09, no. 01, pp. 57–65, 2010, doi: 10.4236/jmmce.2010.91005.
- [15] S. A. Mohan Krishna, T. N. Shridha, and L. Krishnamurthy, "Experimental Investigations on Thermal Analysis and Thermal Characterization of Al 6061-Sic-Gr Hybrid Metal Matrix Composites," *Int. J. Mater. Sci.*, vol. 5, no. 2, pp. 54–66, 2015, doi: 10.12783/ijmsci.2015.0502.04.
- [16] T. Kimoto and J. A. Cooper, *Fundamentals of Silicon Carbide Technology: Growth, Characterization, Devices, and Applications*, 1st ed. Wiley, 2014. doi: 10.1002/9781118313534.
- [17] C. A. Zorman and R. J. Parro, "Micro- and nanomechanical structures for silicon carbide MEMS and NEMS," *Phys. Status Solidi B*, vol. 245, no. 7, pp. 1404–1424, Jul. 2008, doi: 10.1002/pssb.200844135.
- [18] B. C. Pai, G. Ramani, R. M. Pillai, and K. G. Satyanarayana, "Role of magnesium in cast aluminium alloy matrix composites," *J. Mater. Sci.*, vol. 30, no. 8, pp. 1903–1911, Apr. 1995, doi: 10.1007/BF00353012.

- [19] Y. Lu, M. Li, W. Huang, and H. Jiang, "Deformation behavior and microstructural evolution during the semi-solid compression of Al-4Cu-Mg alloy," *Mater. Charact.*, vol. 54, no. 4-5, pp. 423-430, May 2005, doi: 10.1016/j.matchar.2005.01.013.
- [20] M. Rosso, "Thixocasting and rheocasting technologies, improvements going on," *J. Achiev. Mater. Manuf. Eng.*, vol. 54, no. 1, 2012.
- [21] G. Hirt, R. Cremer, T. Witulski, and H.-C. Tinius, "Lightweight near net shape components produced by thixoforming," *Mater. Des.*, vol. 18, no. 4-6, pp. 315-321, Dec. 1997, doi: 10.1016/S0261-3069(97)00071-X.
- [22] O. Lashkari and R. Ghomashchi, "The implication of rheology in semi-solid metal processes: An overview," *J. Mater. Process. Technol.*, vol. 182, no. 1-3, pp. 229-240, Feb. 2007, doi: 10.1016/j.jmatprotec.2006.08.003.
- [23] D. Prayitno and F. A. Apriandini, "Pengaruh Waktu Tahan pada Proses Artificial Aging Terhadap Kekerasan Paduan Al-Sn-Cu," *J. Penelit. DAN KARYA Ilm. Lemb. Penelit. Univ. TRISAKTI*, vol. 4, no. 1, pp. 1-5, Feb. 2019, doi: 10.25105/pdk.v4i1.4009.
- [24] A. R. Ridhowati, E. Febriyanti, and R. Riastuti, "Pengaruh Persentase Reduksi Warm Rolling Terhadap Sifat Mekanik Paduan Cu-Zn 70/30," vol. 16, 2016.
- [25] M. Kouzeli and A. Mortensen, "Size dependent strengthening in particle reinforced aluminium," *Acta Mater.*, vol. 50, no. 1, pp. 39-51, Jan. 2002, doi: 10.1016/S1359-6454(01)00327-5.
- [26] S. Anthreas, "Destructive Testing," in *Project Execution of Mega-Projects for the Oil and Gas Industries*, 1st ed., CRC Press, 2021, pp. 141-141. doi: 10.1201/9781003131656-45.
- [27] S. Sunarno and Z. Zainuddin, "Impact Test Analysis on Steel Metal Materials and Aluminum," *J. Soc. Res.*, vol. 2, no. 7, pp. 2378-2392, Jun. 2023, doi: 10.55324/josr.v2i7.1198.
- [28] J. Edwards, "Hardness Testing," in *Characterization of Materials*, 1st ed., E. N. Kaufmann, Ed., Wiley, 2012, pp. 1-9. doi: 10.1002/0471266965.com025.pub2.

- [29] W.-H. Wu, J.-C. Lee, and Y.-M. Wang, "A Study of Defect Detection Techniques for Metallographic Images," *Sensors*, vol. 20, no. 19, p. 5593, Sep. 2020, doi: 10.3390/s20195593.
- [30] D. N. Leonard, G. W. Chandler, and S. Seraphin, "Scanning Electron Microscopy," in *Characterization of Materials*, 1st ed., E. N. Kaufmann, Ed., Wiley, 2012, pp. 1–16. doi: 10.1002/0471266965.com081.pub2.
- [31] W. Püttgen, W. Bleck, G. Hirt, and H. Shimahara, "Thixoforming of Steels – A Status Report," *Adv. Eng. Mater.*, vol. 9, no. 4, pp. 231–245, Apr. 2007, doi: 10.1002/adem.200700006.
- [32] A. Lanzutti, J. Srnc Novak, F. De Bona, D. Bearzi, M. Magnan, and L. Fedrizzi, "Failure analysis of cemented carbide roller for cold rolling: Material characterisation, numerical analysis, and material modelling," *Eng. Fail. Anal.*, vol. 116, p. 104755, Oct. 2020, doi: 10.1016/j.engfailanal.2020.104755.
- [33] A. Anis, A. Y. Elnour, M. A. Alam, S. M. Al-Zahrani, F. AlFayez, and Z. Bashir, "Aluminum-Filled Amorphous-PET, a Composite Showing Simultaneous Increase in Modulus and Impact Resistance," *Polymers*, vol. 12, no. 9, p. 2038, Sep. 2020, doi: 10.3390/polym12092038.
- [34] J. A. Muñoz, M. Avalos, N. Schell, H. G. Brokmeier, and R. E. Bolmaro, "Comparison of a low carbon steel processed by Cold Rolling (CR) and Asymmetrical Rolling (ASR): Heterogeneity in strain path, texture, microstructure and mechanical properties," *J. Manuf. Process.*, vol. 64, pp. 557–575, Apr. 2021, doi: 10.1016/j.jmapro.2021.02.017.
- [35] G. Falkinger, C. Reisecker, and S. Mitsche, "Analysis of the evolution of Mg<sub>2</sub>Si precipitates during continuous cooling and subsequent re-heating of a 6061 aluminum alloy with differential scanning calorimetry and a simple model," *Int. J. Mater. Res.*, vol. 113, no. 4, pp. 316–326, Apr. 2022, doi: 10.1515/ijmr-2021-8443.
- [36] H. Farh, T. Ziar, H. Belghit, M. Khechba, A. E. Noua, and F. Serradj, "The Cold Rolling Effect on the Precipitation Sequence and Microstructural Changes of an Al-Mg-Si Alloy," *Defect Diffus. Forum*, vol. 397, pp. 51–58, Sep. 2019, doi: 10.4028/www.scientific.net/ddf.397.51.

- [37] S. Morankar, M. Mandal, N. Kourra, M. A. Williams, R. Mitra, and P. Srirangam, "X-Ray Tomography Study on Porosity and Particle Size Distribution in In Situ Al-4.5Cu-5TiB<sub>2</sub> Semisolid Rolled Composites," *JOM*, vol. 71, no. 11, pp. 4050–4058, Nov. 2019, doi: 10.1007/s11837-019-03385-z.
- [38] J. M. Kubiak, B. Li, M. Suazo, and R. J. Macfarlane, "Polymer Grafted Nanoparticle Composites with Enhanced Thermal and Mechanical Properties," *ACS Appl. Mater. Interfaces*, vol. 14, no. 18, pp. 21535–21543, May 2022, doi: 10.1021/acsami.2c03797.
- [39] K. Ikeda and T. Kishi, "Matrix Grain Size Effect and Fracture Behavior on Bending Strength and Fracture Toughness in Multi-Toughened Al<sub>2</sub>O<sub>3</sub>," in *Ceramic Engineering and Science Proceedings*, vol. 13, J. B. Wachtman, Ed., Hoboken, NJ, USA: John Wiley & Sons, Inc., 1994, pp. 164–171. doi: 10.1002/9780470313954.ch18.
- [40] Y. Wang and M. Hadfield, "Failure modes of ceramic rolling elements with surface crack defects," *Wear*, vol. 256, no. 1–2, pp. 208–219, Jan. 2004, doi: 10.1016/S0043-1648(03)00409-5.
- [41] H. Conrad and J. Narayan, "On the grain size softening in nanocrystalline materials," *Scr. Mater.*, vol. 42, no. 11, pp. 1025–1030, May 2000, doi: 10.1016/S1359-6462(00)00320-1.
- [42] T. Y. Reddy and E. Zhang, "Effect of Strain-Hardening on The Behaviour of Axially Crushed Cylindrical Tubes," in *Advances in Engineering Plasticity and its Applications*, Elsevier, 1993, pp. 755–762. doi: 10.1016/B978-0-444-89991-0.50101-3.