

DAFTAR PUSTAKA

- [1] Kementerian ESDM RI, 'Besi Indonesia', *Peluang Investasi Besi Indones.*, p. 42, 2022.
- [2] E. Forbes, M. Jefferson, U. Yenial-Arslan, C. Curtis-Morar, and R. O'Donnell, 'Solving the mystery of natural pyrite flotation – A mineralogy-based approach', *Miner. Eng.*, vol. 207, no. October 2023, p. 108544, 2024, doi: 10.1016/j.mineng.2023.108544.
- [3] B. A. Wills and J. A. Finch, 'Froth Flotation', *Wills' Miner. Process. Technol.*, no. 1984, pp. 265–380, 2016, doi: 10.1016/b978-0-08-097053-0.00012-1.
- [4] D. Haryono *et al.*, 'Investigation of column flotation process on sulphide ore using 2-electrode capacitance sensor: The effect of air flow rate and solid percentage', *AIP Conf. Proc.*, vol. 1945, pp. 2–7, 2018, doi: 10.1063/1.5030267.
- [5] B. A. Wills and J. A. Finch, 'Froth Flotation', in *Wills' Mineral Processing Technology*, no. 1984, 2016, pp. 265–380.
- [6] H. Nugraha, A. N. Fitriani, D. Haryono, M. Al Huda, W. P. Taruno, and S. Harjanto, 'Signal characterization of frother dosage effect in two- phase column flotation process using capacitive measurement method', *AIP Conf. Proc.*, vol. 2232, no. April, 2020, doi: 10.1063/5.0001979.
- [7] D. Haryono, I. Darmabakti, S. Oediyani, and S. Harjanto, 'Monitoring of Column Flotation Process in Collection Zone using ECVT with the Effect of Collector and Frother Doses to Recovery', *Mesin*, vol. 11, no. 1, pp. 1–7, 2020, doi: 10.25105/ms.v11i1.7442.

- [8] D. Haryono, S. Harjanto, H. Nugraha, M. Al Huda, and W. P. Taruno, 'Column flotation monitoring based on electrical capacitance volume tomography: A preliminary study', *AIP Conf. Proc.*, vol. 1805, 2017, doi: 10.1063/1.4974436.
- [9] C. K. Gupta, *Chemical Metallurgy Principles and Practice*. 2003.
- [10] R. Prakash, S. K. Majumder, and A. Singh, 'Flotation technique: Its mechanisms and design parameters', *Chem. Eng. Process. - Process Intensif.*, vol. 127, pp. 249–270, 2018, doi: 10.1016/j.cep.2018.03.029.
- [11] B. A. Wills and J. A. Finch, 'Froth Flotation', *Wills' Miner. Process. Technol.*, no. 1984, pp. 265–380, 2016, doi: 10.1016/b978-0-08-097053-0.00012-1.
- [12] National Center for Biotechnology Information, 'PubChem Compound Summary for CID 493949, Potassium pentylxanthate', *PubChem*, 2024. <https://pubchem.ncbi.nlm.nih.gov/compound/Potassium-pentylxanthate> (accessed Dec. 18, 2024).
- [13] D. Wang, 'Flotation reagents', in *Applied Surface Chemistry on Minerals Flotation and Energy Resources Beneficiation: Volume 1: Functional Principle*, 2016, pp. 1–382.
- [14] P. Forson, M. Zanin, W. Skinner, and R. Asamoah, 'Differential flotation of pyrite and arsenopyrite: Effect of hydrogen peroxide and collector type', *Miner. Eng.*, vol. 163, no. December 2020, p. 106808, 2021, doi: 10.1016/j.mineng.2021.106808.
- [15] G. Güven, B. Tunç, B. Aydın, and G. Bulut, 'Effects of frothers on bubbles size and flotation performance of hydrophobic minerals', *J. Cent. South Univ.*, vol. 31, no. 7, pp. 2280–2299, 2024, doi: 10.1007/s11771-024-5685-5.

- [16] J. Yianatos, C. Carrasco, L. Vinnett, and I. Rojas, 'Pyrite recovery mechanisms in rougher flotation circuits', *Miner. Eng.*, vol. 66, pp. 197–201, 2014, doi: 10.1016/j.mineng.2014.03.020.
- [17] A. Azizi, 'Influence of collector dosage and pulp chemistry on copper flotation', *Geosystem Eng.*, vol. 17, no. 6, pp. 311–316, 2014, doi: 10.1080/12269328.2014.994787.
- [18] S. Bahtiar, W. Muzakki, R. Desiasni, F. Widyawati, and S. Hidayat, 'Pengaruh Ukuran Partikel, Persen Padatan, dan pH pada Proses Flotasi Terhadap Perolehan Kembali Tembaga', *J. Pijar Mipa*, vol. 16, no. 3, pp. 406–410, 2021, doi: 10.29303/jpm.v16i3.1308.
- [19] S. M. Siagian, G. W. Jaya, and I. Nurhidayati, 'Analisis Jumlah Muatan Listrik Serta Energi Pada Kapasitor Berdasarkan Konstanta Dielektrik Suatu Material', *ORBITA J. Kajian, Inov. dan Apl. Pendidik. Fis.*, vol. 7, no. 1, p. 176, 2021, doi: 10.31764/orbita.v7i1.4420.
- [20] M. Sidi, B. P. Lapanporo, and Y. Arman, 'Perbandingan Kapasitansi dari Beberapa Jenis Bahan Menggunakan Kapasitor Silinder', *Prism. Fis.*, vol. 8, no. 2, p. 128, 2020, doi: 10.26418/pf.v8i2.42528.
- [21] B. E. Cahyono, M. Misto, and F. Hasanah, 'Karakterisasi Sensor Kapasitif Untuk Penentuan Level Aquades', *Rekayasa Energi Manufaktur*, vol. 1, no. 2, p. 9, 2016, doi: 10.21070/r.e.m.v1i2.583.
- [22] F. Ningsih, F. Fitriarningsih, and L. A. Didik, 'Analisis Pengaruh Lama Penggerusan Terhadap Resistivitas Dan Konstanta Dielektrik Pada Pasir Besi Yang Disintesis Dari Kabupaten Bima', *Indones. Phys. Rev.*, vol. 2, no. 3, pp. 92–98, 2019, doi: 10.29303/ipr.v2i3.31.
- [23] A. Yusuf, W. Widada, and W. P. Taruno, 'Determine of the Time Constant of Capacitance Applied to Electrical Capacitance Tomography', *2022 Int.*

Conf. Informatics Electr. Electron. ICIEE 2022 - Proc., pp. 1–6, 2022, doi: 10.1109/ICIEE55596.2022.10010084.

- [24] J. Maitre, K. Bouchard, and L. P. Bédard, ‘Computers and Geosciences Mineral grains recognition using computer vision and machine learning’, *Comput. Geosci.*, vol. 130, no. May, pp. 84–93, 2019, doi: 10.1016/j.cageo.2019.05.009.
- [25] W. Wang and L. Wang, ‘An Image Processing Method for Grains Counting’, pp. 181–185, 2012.
- [26] M. Ostadrahimi, S. Farrokhpay, K. Gharibi, A. Dehghani, and M. Aghajanloo, ‘Effects of flotation operational parameters on froth stability and froth recovery’, *J. South. African Inst. Min. Metall.*, vol. 121, no. 1, pp. 11–20, 2021, doi: 10.17159/2411-9717/1272/2021.
- [27] A. Eskanolou, M. R. Khalesi, M. Abdollahy, and M. H. Chegeni, ‘Interactional effects of bubble size, particle size, and collector dosage on bubble loading in column flotation’, *J. Min. Environ.*, vol. 9, no. 1, pp. 107–116, 2017, doi: 10.22044/jme.2017.5815.1393.
- [28] A. Eskanolou, M. R. Khalesi, M. Abdollahy, and M. H. Chegeni, ‘Interactional effects of bubble size, particle size, and collector dosage on bubble loading in column flotation’, *J. Min. Environ.*, no. September, 2017, doi: 10.22044/jme.2017.5815.1393.
- [29] S. Oediyani, A. Muttaqin, D. Haryono, and R. F. Suwandana, ‘Metallurgical performance of column and mechanical flotation as a rougher circuit in sphalerite ore flotation with %solid and frother dose variation’, *IOP Conf. Ser. Mater. Sci. Eng.*, vol. 909, no. 1, 2020, doi: 10.1088/1757-899X/909/1/012010.
- [30] R. Soltanpour, M. Irannajad, and F. Nakhaei, ‘Investigation of effective

operating parameters on carrying capacity in column flotation of copper sulfide minerals', *Part. Sci. Technol.*, vol. 37, no. 6, pp. 677–684, 2019, doi: 10.1080/02726351.2018.1435593.

- [31] A. Uribe-Salas, P. de Lira-Gómez, R. Pérez-Garibay, F. Nava-Alonso, L. Magallanes-Hernández, and C. Lara-Valenzuela, 'Overloading of gas bubbles in column flotation of coarse particles and effect upon recovery', *Int. J. Miner. Process.*, vol. 71, no. 1–4, pp. 167–178, 2003, doi: 10.1016/S0301-7516(03)00036-X.
- [32] D. Haryono, H. Nugraha, M. Al Huda, W. P. Taruno, and S. Harjanto, 'The Effect of Flotation Reagents Addition (MIBC and PAX) on the Relative Permittivity Value Using 2-Electrode Capacitance Sensor', *Procedia Eng.*, vol. 170, pp. 369–372, 2017, doi: 10.1016/j.proeng.2017.03.059.